



ICONIC BRANDS, LEADING INNOVATION

MERCHANDISER REFRIGERATORS & FREEZERS

Countertop & Upright Models



040722



www.maxx-cold.com

3355 Enterprise Avenue, Suite 160 | Fort Lauderdale, FL 33331
Tel: 954.202.7419 | Fax: 954.202.7337 | www.maxx-cold.com

A DIVISION OF
THE LEGACY COMPANIES 



MXM1-12RHC
25"W x 26"D x 62"H



MXM1-12RBHC
25"W x 26"D x 62"H



MXM1-16RHC
25"W x 26"D x 74.5"H



MXM1-16RBHC
25"W x 26"D x 74.5"H



MXM1-23RHC
27"W x 32"D x 79.5"H



MXM1-23RBHC
27"W x 32"D x 79.5"H

Models:

MXM1-12RHC - Reach-in refrigerator; white coated steel exterior

MXM1-12RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16RHC - Reach-in refrigerator; white coated steel exterior

MXM1-16RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23RHC - Reach-in refrigerator; white coated steel exterior

MXM1-23RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12RHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12RBHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RBHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23RHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23RBHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER REFRIGERATORS



MXM2-48RHC
54"W x 32"D x 79.5"H



MXM2-48RBHC
54"W x 32"D x 79.5"H



MXM3-72RHC
81"W x 32"D x 79.5"H



MXM3-72RBHC
81"W x 32"D x 79.5"H

Models:

MXM2-48RHC - Reach-in refrigerator; white coated steel exterior

MXM2-48RBHC - Reach-in refrigerator; black coated steel exterior

MXM3-72RHC - Reach-in refrigerator; white coated steel exterior

MXM3-72RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72RHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72RBHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph



MXM2-48RSHC
54"W x 32"D x 79.5"H



MXM2-48RSBHC
54"W x 32"D x 79.5"H

Models:

MXM2-48RSHC - Reach-in sliding door refrigerator; white coated steel exterior

MXM2-48RSBHC - Reach-in sliding door refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Supplied with eight (8) adjustable heavy-duty PE-coated wire shelves
- Equipped with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RSHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RSBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER FREEZERS



MXM1-12FHC
25"W x 26"D x 62"H



MXM1-12FBHC
25"W x 26"D x 62"H



MXM1-16FHC
25"W x 26"D x 74.5"H



MXM1-16FBHC
25"W x 26"D x 74.5"H



MXM1-23FBHC
27"W x 32"D x 79.5"H



MXM1-23FBHC
27"W x 32"D x 79.5"H

Models:

MXM1-12FHC - Reach-in refrigerator; white coated steel exterior

MXM1-12FBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16FHC - Reach-in refrigerator; white coated steel exterior

MXM1-16FBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23FHC - Reach-in refrigerator; white coated steel exterior

MXM1-23FBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane heated & insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12FHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12FBHC	25" x 26" x 62" (635 x 660 x 1575 mm)	20.25" x 20.5" x 23.5" (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FBHC	25" x 26" x 74.5" (635 x 660 x 1900 mm)	20.25" x 20.5" x 49.125" (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23FHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23FBHC	27" x 32" x 79.5" (686 x 810 x 2019 mm)	26.5" x 22" x 52.25" (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph



MXM2-48FHC
54"W x 32"D x 79.5"H



MXM2-48FBHC
54"W x 32"D x 79.5"H



MXM3-72FHC
81"W x 32"D x 79.5"H



MXM3-72FBHC
81"W x 32"D x 79.5"H

Models:

MXM2-48FHC - Reach-in refrigerator; white coated steel exterior

MXM2-48FBHC - Reach-in refrigerator; black coated steel exterior

MXM3-72FHC - Reach-in refrigerator; white coated steel exterior

MXM3-72FBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane, heated, insulated self-closing glass doors
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48FHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48FBHC	54" x 32" x 79.5" (1372 x 810 x 2019 mm)	49.25" x 26.5" x 52.25" (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72FHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72FBHC	81" x 32" x 79.5" (2057 x 810 x 2019 mm)	72.25" x 26.5" x 52.25" (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph

UPRIGHT NARROW WIDTH MERCHANDISER REFRIGERATORS



MXM2-36RHC
39.5"W x 33.5"D x 79.5"H



MXM2-36RBHC
39.5"W x 33.5"D x 79.5"H



MXM2-36RSHC
39.5"W x 33.5"D x 79.5"H



MXM2-36RSBHC
39.5"W x 33.5"D x 79.5"H



Models:

MXM2-36RHC - Reach-in refrigerator; white coated steel exterior

MXM2-36RBHC - Reach-in refrigerator; black coated steel exterior

MXM2-36RSHC - Reach-in sliding door refrigerator; white coated steel exterior

MXM2-36RSBHC - Reach-in sliding door refrigerator; black coated steel exterior

All Models Feature:

- Nominal Storage Capacity:
 - MXM2-36RHC/36RBHC.....36 Cu Ft (1019 L)
 - MXM2-36RSHC/36RSBHC.....36 Cu Ft (1019 L)
- Smooth, powder coated steel exterior available in either white or black
- Low-e double pane glass doors
- Four (4) adjustable heavy-duty PE-coated wire shelves per door, include pricing strips
- Electronic thermostat and digital LED temperature display
- HC refrigerant R290
- CFC refrigerant and foam insulation
- Self-closing swing doors or sliding doors available, both are provided with lock and key set for security
- Automatic defrost system, equipped with integrated condensate pan therefore no drain line connection is needed
- Interior LED lighting
- Designed with an illuminated plastic merchandising top panel



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-36RHC	39.5" x 33.5" x 79.5" (1119 x 851 x 2019 mm)	35" x 27.6" x 52.4" (889 x 701 x 1331 mm)	36 Cu Ft (1019 L)	33°F to 41°F (1°C to 5°C)	4.5A	430 lbs (196 kg)	R-290A 3.07 oz (105 g)	2 Swing / 4 Shelves	115V / 60Hz / 1Ph
MXM2-36RBHC	39.5" x 33.5" x 79.5" (1119 x 851 x 2019 mm)	35" x 27.6" x 52.4" (889 x 701 x 1331 mm)	36 Cu Ft (1019 L)	33°F to 41°F (1°C to 5°C)	4.5A	430 lbs (196 kg)	R-290A 3.07 oz (105 g)	2 Swing / 4 Shelves	115V / 60Hz / 1Ph
MXM2-36RSHC	39.5" x 31" x 79.5" (1119 x 787 x 2019 mm)	35" x 22.7" x 52.4" (889 x 577 x 1331 mm)	36 Cu Ft (1019 L)	33°F to 41°F (1°C to 5°C)	4.5A	430 lbs (196 kg)	R-290A 3.07 oz (105 g)	2 Sliding / 4 Shelves	115V / 60Hz / 1Ph
MXM2-36RSBHC	39.5" x 31" x 79.5" (1119 x 787 x 2019 mm)	35" x 22.7" x 52.4" (889 x 577 x 1331 mm)	36 Cu Ft (1019 L)	33°F to 41°F (1°C to 5°C)	4.5A	430 lbs (196 kg)	R-290A 3.07 oz (105 g)	2 Sliding / 4 Shelves	115V / 60Hz / 1Ph



MXM2-36FHC
39.5"W x 33.5"D x 79.5"H



MXM2-36FBHC
39.5"W x 33.5"D x 79.5"H

Models:

MXM2-36FHC - Reach-in sliding door freezer; white coated steel exterior

MXM2-36FBHC - Reach-in sliding door freezer; black coated steel exterior

All Models Feature:

- Nominal Storage Capacity:
 - MXM2-36FHC/36FBHC.....36 Cu Ft (1019 L)
- Smooth, powder coated steel exterior available in either white or black
- Low-e triple pane glass doors
- Four (4) adjustable heavy-duty PE-coated wire shelves per door, include pricing strips
- Electronic thermostat and digital LED temperature display
- HC refrigerant R290
- CFC refrigerant and foam insulation
- Self-closing doors are provided with lock and key set for security
- Automatic defrost system, equipped with integrated condensate pan therefore no drain line connection is needed
- Interior LED lighting
- Designed with an illuminated plastic merchandising top panel



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-36FHC	39.5" x 33.5" x 79.5" (1119 x 851 x 2019 mm)	35" x 27.6" x 52.4" (889 x 701 x 1331 mm)	36 Cu Ft (1019 L)	-4°F to 10°F (-20°C to -12°C)	12.0A	450 lbs (205 kg)	R-290A 5.29 oz (150 g)	2 Swing / 4 Shelves	115V / 60Hz / 1Ph
MXM2-36FBHC	39.5" x 33.5" x 79.5" (1119 x 851 x 2019 mm)	35" x 27.6" x 52.4" (889 x 701 x 1331 mm)	36 Cu Ft (1019 L)	-4°F to 10°F (-20°C to -12°C)	12.0A	450 lbs (205 kg)	R-290A 5.29 oz (150 g)	2 Swing / 4 Shelves	115V / 60Hz / 1Ph

UPRIGHT LARGE CAPACITY MERCHANDISER REFRIGERATORS



MXGDM-30RBHC
27"W x 33.5"D x 79.5"H



MXGDM-50RBHC
54"W x 33.5"D x 79.5"H

COMING SOON



MXGDM-73RBHC
81"W x 33.5"D x 79.5"H



Models:

MXGDM-30RBHC - Reach-in refrigerator; black coated steel exterior

MXGDM-50RBHC - Reach-in refrigerator; black coated steel exterior

MXGDM-73RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Nominal Storage Capacity:
 - MXGDM-30RBHC.....30 Cu Ft (850 L)
 - MXGDM-50RBHC.....50 Cu Ft (1416 L)
 - MXGDM-73RBHC.....73 Cu Ft (2067 L)
- Constructed of a powder coated steel black exterior and white interior
- Low-e double pane glass doors
- Bottom mounted compressor
- Four (4) adjustable heavy-duty PE-coated wire shelves per door, include pricing strips
- Four (4) rollers (2 with leveling feet) - 1 Door & 2 Door models
- Six (6) rollers (3 with leveling feet) - 3 Door models
- Electronic thermostat and digital LED temperature display provide accurate and easy reading
- Self-closing doors are provided with lock and key set for security
- Magnetic gasket can be replaced without tools
- CFC free refrigerant and foam
- Automatic defrost system, equipped with integrated condensate pan therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXGDM-30RBHC	27" x 33.5" x 79.5" (686 x 851 x 2019 mm)	22" x 26.5" x 52.25" (559 x 673 x 1327 mm)	30 Cu Ft (850 L)	33°F to 41°F (1°C to 5°C)	3.0A	331 lbs (151 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph
MXGDM-50RBHC	54" x 33.5" x 79.5" (1372 x 851 x 2019 mm)	49.4" x 26.5" x 52.25" (1255 x 673 x 1327 mm)	50 Cu Ft (1416 L)	33°F to 41°F (1°C to 5°C)	4.5A	540 lbs (245 kg)	R-290A 3.7 oz (105 g)	2 / 8	115V / 60Hz / 1Ph
MXGDM-73RBHC	81" x 33.5" x 79.5" (2057 x 851 x 2019 mm)	76.4" x 26.5" x 52.25" (1941 x 673 x 1327 mm)	73 Cu Ft (2067 L)	33°F to 41°F (1°C to 5°C)	7.0A	741 lbs (337 kg)	R-290A 5.29 oz (150 g)	3 / 12	115V / 60Hz / 1Ph



MXGDM-30FBHC
27"W x 33.5"D x 79.5"H



MXGDM-50FBHC
54"W x 33.5"D x 79.5"H



MXGDM-73FBHC
81"W x 33.5"D x 79.5"H

COMING SOON

Models:

MXGDM-30FBHC - Reach-in freezer; black coated steel exterior

MXGDM-50FBHC - Reach-in freezer; black coated steel exterior

MXGDM-73FBHC - Reach-in freezer; black coated steel exterior

All Models Feature:

- Nominal Storage Capacity:
 - MXGDM-30FBHC.....30 Cu Ft (850 L)
 - MXGDM-50FBHC.....50 Cu Ft (1416 L)
 - MXGDM-73FBHC.....73 Cu Ft (2067 L)
- Constructed of a powder coated steel black exterior and white interior
- Low-e triple pane glass doors
- Bottom mounted compressor
- Four (4) adjustable heavy-duty PE-coated wire shelves per door, include pricing strips
- Four (4) rollers (2 with leveling feet) - 1 Door & 2 Door models
- Six (6) rollers (3 with leveling feet) - 3 Door models
- Electronic thermostat and digital LED temperature display provide accurate and easy reading
- Self-closing doors are provided with lock and key set for security
- Magnetic gasket can be replaced without tools
- CFC free refrigerant and foam
- Automatic defrost system, equipped with integrated condensate pan therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXGDM-30FBHC	27" x 33.5" x 79.5" (686 x 851 x 2019 mm)	22" x 26.5" x 52.25" (559 x 673 x 1327 mm)	30 Cu Ft (850 L)	-4°F to 10°F (-20°C to -12°C)	8.0A	353 lbs (161 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph
MXGDM-50FBHC	54" x 33.5" x 79.5" (1372 x 851 x 2019 mm)	49.4" x 26.5" x 52.25" (1255 x 673 x 1327 mm)	50 Cu Ft (1416 L)	-4°F to 10°F (-20°C to -12°C)	9.0A	567 lbs (257 kg)	R-290A 5.29 oz (150 g)	2 / 8	115V / 60Hz / 1Ph
MXGDM-73FBHC	81" x 33.5" x 79.5" (2057 x 851 x 2019 mm)	76.4" x 26.5" x 52.25" (1941 x 673 x 1327 mm)	73 Cu Ft (2067 L)	-4°F to 10°F (-20°C to -12°C)	9.0A	829 lbs (376 kg)	R-290A 5.29 oz (150 g)	3 / 12	115-230V / 60Hz / 1Ph



COMING SOON

MXM1-23FHC-ICE
27"W x 33.5"D x 79.5"H



COMING SOON

MXM2-48FHC-ICE
54"W x 33.5"D x 79.5"H



Models:

MXM1-23FHC-ICE - Reach-in freezer; white coated steel exterior

MXM2-48FHC-ICE - Reach-in freezer; white coated steel exterior

All Models Feature:

- Nominal Storage Capacity:
 - MXM1-23FCH-ICE.....23 Cu Ft (651 L)
 - MXM2-48FCH-ICE.....48 Cu Ft (1359 L)
- Constructed of a white powder coated steel exterior and interior
- Low-e triple pane glass doors
- Bottom mounted compressor
- One (1) heavy-duty PE-coated floor support with customer facing bag retainer per section
- Four (4) rollers (2 with leveling feet)
- Electronic thermostat and digital LED temperature display provides accurate and easy reading
- Self-closing doors are provided with lock and key set for security
- Magnetic gasket can be replaced without tools
- CFC free refrigerant and foam
- Automatic defrost system, equipped with integrated condensate pan therefore no drain line connection is needed
- Designed with an illuminated plastic merchandising top panel



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS	ELECTRICAL
MXM1-23FHC-ICE	27" x 33.5" x 79.5" (686 x 851 x 2019 mm)	22.2" x 27.6" x 52.4" (564 x 701 x 1331 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	353 lbs (161 kg)	R-290A 3.88 oz (110 g)	1	115V / 60Hz / 1Ph
MXM2-48FHC-ICE	54" x 33.5" x 79.5" (1372 x 851 x 2019 mm)	49.4" x 7.6" x 52.4" (1255 x 701 x 1331 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	9.0A	567 lbs (258 kg)	R-290A 5.29 oz (150 g)	2	115V / 60Hz / 1Ph



MXM1-2RHC
MXM1-2FHC
22.4"W x 22"D x 20.9"H



MXM1-2.5FHC
22.4"W x 22"D x 20.9"H



MXM1-3.5RHC
MXM1-3.5FHC
22.4"W x 22"D x 20.9"H



MXM1-4FHC
22.4"W x 22"D x 20.9"H

Refrigerators:

MXM1-2RHC - Reach-in refrigerator; coated steel exterior

MXM1-3.5RHC - Reach-in refrigerator; coated steel exterior

Freezers:

MXM1-2FHC - Reach-in freezer; coated steel exterior

MXM1-2.5FHC - Reach-in freezer; coated steel exterior

MXM1-3.5FHC - Reach-in freezer; coated steel exterior

MXM1-4FHC - Reach-in freezer; coated steel exterior

All Models Feature:

- Constructed of white painted steel exterior and ABS interior
- Multi-pane, self-closing glass door with magnetic compression gaskets
- Interior LED lighting
- Bottom mounted compressor
- Equipped with adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) adjustable leveling feet
- Digital controls with LED temperature display
- Automatic defrost cycle
- Provided with lock and key set for security
- Foamed urethane insulation to improve temperature regulation
- Supplied with integrated condensate evaporator therefore no drain line connection is needed



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-2RHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	33°F to 41°F (1°C to 5°C)	1.2A	94.8 lbs (43 kg)	R-600A 1.41 oz (40 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5RHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	33°F to 41°F (1°C to 5°C)	1.2A	117 lbs (53 kg)	R-600A 1.76 oz (50 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-2FHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	101.4 lbs (46 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-2.5FHC	22.4" x 22" x 28.7" (569 x 558 x 729 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.6 Cu Ft (73.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	115 lbs (52 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5FHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	0°F to 10°F (-18°C to -12°C)	2.5A	123.5 lbs (56 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-4FHC	22.4" x 22" x 35" (569 x 558 x 889 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	4.2 Cu Ft (119 L)	0°F to 10°F (-18°C to -12°C)	2.5A	143 lbs (65 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph

4-SIDED GLASS COUNTERTOP MERCHANDISER REFRIGERATORS



MECR-31D
16.7"W x 15.9"D x 38.6"H



MECR-32D
16.7"W x 15.9"D x 38.6"H

Models:

MECR-31D - Reach-in refrigerator; white coated steel exterior

MECR-32D - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Durable, corrosion resistant black painted steel and stainless steel exterior with black plastic trim
- Easy to clean, low maintenance ABS interior
- Dual pane tempered glass doors and sides prevent heat loss and minimize condensation
- Interior LED lighting
- Digital controls deliver precise temperature regulation
- Internal bottom mounted compressor with flow through ventilation to cool the utility compartment
- Manual defrost cycle maintains ideal storage conditions
- Internal condensate evaporator pan included, so no drain connection is needed
- Flat top accommodates POP or other marketing displays
- Three (3) heavy-duty, adjustable chrome-plated wire shelves
- 2" legs (two front adjustable leveling legs)



MODEL	EXTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MECR-31D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	84.9 lbs (38.5 kg)	R-290A 1.41 oz (40 g)	1 / 3	115V / 60Hz / 1Ph
MECR-32D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	86 lbs (39 kg)	R-290A 1.41 oz (40 g)	2 / 3	115V / 60Hz / 1Ph