



MAXX COLD

ICONIC BRANDS, LEADING INNOVATION

**Dipping Cabinets
Ice Cream Display Freezers**





MXDC-4
31.5"W x 27.2"D x 50.4"H



MXDC-8
51.7"W x 27.2"D x 50.4"H



MXDC-12
70"W x 27.2"D x 50.4"H

Models:

MXDC-4 - Dipping cabinet; coated steel exterior

MXDC-8 - Dipping cabinet coated steel exterior

MXDC-12 - Dipping cabinet; coated steel exterior

All Models Feature:

- Exterior Material: durable, white powder coated steel
- Interior Material: white powder coated steel
- Tub Holders: coated wire with acrylic covers
- Insulation: 2.5" foamed in-place polyurethane
- Flat, tempered clear glass sliding lids
- Lock and key set with removable pin
- Interior LED lighting enhances product's appearance
- Curved tempered glass sneeze guard (assembly required)
- Heated molded plastic lid frame prevents frost build-up
- Internal condensate evaporator pan, no floor drain needed
- Bottom defrost drain with plug
- Four (4) heavy-duty casters, two (2) with brakes
- Removable rubber bumper guards, grill side
- Plastic frost scraper included
- Adjustable temperature range -18°F to +10°F (-28°C to -12°C)
- Thermometer display: external, digital, easily read
- Includes: Hanging tub holders and spill skirts

Optional Accessories (Sold Separately):

- Dipper well with faucet #XDCWELL



- Zeroll® scoops and spades (Various models available - inquire for info)



- Gelato pans #XDCPAN-5



- Gelato pan holders & Novelty baskets #XDCBASKET3 / #XDCBASKETN3



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	TOTAL TUB STORAGE	TUBS EXPOSED FOR SCOOPING	ELECTRICAL
MXDC-4	31.5" x 27.2" x 50.4" (800 x 691 x 1280 mm)	25.5" x 21.5" x 26.5" (648 x 546 x 673 mm)	6.5 Cu Ft (184 L)	-18°F to 10°F (-28°C to -12°C)	1.3A	184 lbs (83 kg)	R290 2.65 oz (75 g)	6	4	115V / 60Hz / 1Ph
MXDC-8	51.7" x 27.2" x 50.4" (1313 x 691 x 1280 mm)	46.5" x 21.5" x 26.5" (1181 x 546 x 673 mm)	8.8 Cu Ft (249 L)	-18°F to 10°F (-28°C to -12°C)	2.0A	262 lbs (119 kg)	R290 3.6 oz (102 g)	14	8	115V / 60Hz / 1Ph
MXDC-12	70" x 27.2" x 50.4" (1778 x 691 x 1280 mm)	65.5" x 21.5" x 26.5" (1664 x 546 x 673 mm)	11.1 Cu Ft (314 L)	-18°F to 10°F (-28°C to -12°C)	4.1A	320 lbs (145 kg)	R290 4.76 oz (135 g)	22	12	115V / 60Hz / 1Ph



MXF31F

31.5"W x 27.2"D x 50.4"H



MXF52F

51.7"W x 27.2"D x 50.4"H



MXF71F

70"W x 27.2"D x 50.4"H

Models:

MXF31F - Mobile ice cream freezer; coated steel exterior

MXF52F - Mobile ice cream freezer; coated steel exterior

MXF71F - Mobile ice cream freezer; coated steel exterior

All Models Feature:

- Exterior Material: durable, white powder coated steel
- Interior Material: white power coated steel
- Flat coated wire baskets with 3 compartments each
- Insulation: 2.5" foamed in-place polyurethane
- Flat, tempered clear glass sliding lids
- Lock and key set with removable pin
- Interior LED lighting enhances product's appearance
- Heated molded plastic lid frame prevents frost build-up
- Internal condensate evaporator pan, no floor drain needed
- Bottom defrost drain with plug
- Four (4) or six (6) heavy-duty casters, two (2) with brakes
- Removable rubber bumper guards, grill side
- Plastic frost scraper included
- Adjustable temperature range -18°F to +10°F (-28°C to -12°C)
- Thermometer display: external, analog, easily read
- Includes: Novelty baskets

Optional Accessories (Sold Separately):

- Zeroll® scoops and spades (Various models available - inquire for info)
- Gelato pans
- Gelato pan holders & Novelty baskets
- Double 3-gallon tub hanging baskets with skirt



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	BASKETS	ELECTRICAL
MXF31F	31.5" x 27.2" x 50.4" (800 x 690 x 1280 mm)	25.5" x 21.5" x 26.5" (648 x 546 x 673 mm)	5.8 Cu Ft (164 L)	-18°F to 10°F (-28°C to -12°C)	1.3A	130 lbs (59 kg)	R290 2.65 oz (75 g)	2	115V / 60Hz / 1Ph
MXF52F	51.7" x 27.2" x 50.4" (1313 x 690 x 1280 mm)	40" x 25.2" x 13.9" (1017 x 639 x 353 mm)	11 Cu Ft (312 L)	-18°F to 10°F (-28°C to -12°C)	2.0A	179 lbs (81 kg)	R290 3.6 oz (102 g)	4	115V / 60Hz / 1Ph
MXF71F	70" x 27.2" x 50.4" (1778 x 690 x 1280 mm)	52" x 25.2" x 13.9" (1320 x 639 x 353 mm)	16 Cu Ft (453 L)	-18°F to 10°F (-28°C to -12°C)	4.1A	219 lbs (99 kg)	R290 4.76 oz (135 g)	5	115V / 60Hz / 1Ph



MXF25CHC-2
24.6"W x 27.6"D x 32.6"H



MXF32CHC-3
31.5"W x 27.5"D x 33.5"H



MXF40CHC-4
39.4"W x 27.5"D x 33.5"H



MXF48CHC-5
47.4"W x 27.5"D x 33.5"H



MXF54CHC-6
53.2"W x 27.5"D x 33.5"H



MXF64CHC-7
63.4"W x 27.5"D x 33.5"H



MXF72CHC-8
71.7"W x 27.5"D x 33.5"H

Models:

MXF25CHC-2 - Mobile ice cream freezer; coated steel exterior
MXF32CHC-3 - Mobile ice cream freezer; coated steel exterior
MXF40CHC-4 - Mobile ice cream freezer; coated steel exterior
MXF48CHC-5 - Mobile ice cream freezer; coated steel exterior

MXF54CHC-6 - Mobile ice cream freezer; coated steel exterior
MXF64CHC-7 - Mobile ice cream freezer; coated steel exterior
MXF72CHC-8 - Mobile ice cream freezer; coated steel exterior

All Models Feature:

- Clear, curved glass sliding lids
- Easy grip sliding lid handle
- Lid lock and keys
- Interior LED lights makes it easier to see selection and enhance product's appearance
- Molded plastic lid frame heated to prevent frost or ice build-up
- Internal condensate evaporator pan. No need for a floor drain.
- Equipped with four (4) or six (6) heavy-duty casters
- Removable rubber bumper guards, side grill



MODEL	EXTERIOR DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	REFRIGERANT AND CHARGE SIZE	UNIT WEIGHT	AMP DRAW	HP	INCLUDED BASKETS
MXF25CHC-2	24.6 x 27.6 x 32.6 625 x 700 x 828 mm	3.81 Cu Ft 108 L	-18°F to 10°F (-28°C to -12°C)	R290a 2.43 oz / 69 g	103.6 lb 47 kg	1.0A	1/9	2
MXF32CHC-3	31.5 x 27.5 x 33.5 800 x 697 x 850 mm	4.87 Cu Ft 138 L	-18°F to 10°F (-28°C to -12°C)	R290a 2.65 oz / 75 g	114.6 lb 52 kg	1.3A	1/7	3
MXF40CHC-4	39.4 x 27.5 x 33.5 1000 x 697 x 850 mm	6.71 Cu Ft 190 L	-18°F to 10°F (-28°C to -12°C)	R290a 3 oz / 85 g	130.1 lb 59 kg	1.4A	1/5	4
MXF48CHC-5	47.4 x 27.5 x 33.5 1204 x 697 x 850 mm	8.62 Cu Ft 244 L	-18°F to 10°F (-28°C to -12°C)	R290a 3.53 oz / 100 g	152.1 lb 69 kg	2.0A	1/4	5
MXF54CHC-6	53.2 x 27.5 x 33.5 1350 x 697 x 850 mm	9.96 Cu Ft 282 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.06 oz / 115 g	165.4 lb 75 kg	2.0A	1/4	6
MXF64CHC-7	63.4 x 27.5 x 33.5 1610 x 697 x 850 mm	12.36 Cu Ft 350 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.23 oz / 120 g	187.4 lb 85 kg	2.0A	1/4+	7
MXF72CHC-8	71.7 x 27.5 x 33.5 1820 x 697 x 850 mm	14.30 Cu Ft 405 L	-18°F to 10°F (-28°C to -12°C)	R290a 4.76 oz / 135 g	231.5 lb 105 kg	2.8A	1/2	8