

MENUMASTER[®] Commercial

Project #: _____

Item #: _____



Market Region: **North America**

Chef Line | Heavy Volume
This category of microwave oven is ideal for...

Applications

- Fast casual dining
- Prep stations
- Bars & grills
- Quick service restaurants
- Casual dining
- Convenience stores
- Bakery cafés
- Kiosks
- Food courts

Through put potential by oven wattage (items per hour)

Food item	1000W	1200W	1800W	2100W
Steamed Shrimp (8oz (227g))	22	23	33	38
Scrambled Eggs (4oz (120g))	48	51	65	72
Steamed Rice (8cups (1.2kg))	2	3	5	7
1 Baked potato (9oz (255g))	17	18	21	29
Salmon fillet (8oz (227g))	19	20	26	29
Chocolate Cake in a Cup	57	60	80	97
Fresh Steamed Veggies (6oz (170g))	45	48	65	80
Asparagus (8oz (227g))	29	30	45	51
Dumplings (6ea)	19	19	24	28

All ACP, Inc. commercial ovens are supported by our Culinary Center. Do not hesitate to contact us for any questions regarding food preparation, menu development and cooking times: testkitchen@acpsolutions.com



Heavy Volume MenuMaster[®] Commercial MDC-Y Series

Power Output

- 1000-2100 Watts of power
- Unique method of microwave energy distribution provides superior even heating throughout the entire cavity

Multi-language universal operation, with programming flexibility

- Oven interface and programming software supports 24 languages
- Smart USB connectivity standard
- Compatible with ACP Programming Application

Easy to Use

- Control panel located on bottom for convenient access when installed on shelf
- Up to 100 programmable menu items simplifies cooking
- 11 power levels and 4 cooking stages for cooking flexibility
- Multiple quantity function automatically calculates cooking times for multiple portions
- Automatic Voltage Sensor adjusts to the power supply (**North America only >1200W**)
- See-through door and lighted interior for monitoring without opening the door
- Ample 0.6 cubic ft. (17 liter) capacity accommodates a standard half-sized pan
- Stackable to save valuable counter space

Easy to Maintain

- Stainless steel exterior and interior for easy cleaning and increased durability
- Two side-mounted, removable, cleanable air filter protect oven components
- Constructed to withstand the foodservice environment, multiple users and variable ambient temperatures
- Gasket sealed Borosilicate Glass tray for easy cleaning
- Interlock switch assembly is engineered for maximum durability and long life

Optional Accessories

- Cavity shelf (SE10)
- Stainless cart/equipment stands: (CA24, CA30)
- Non-stick baskets (TB10/S, SB10/S, MB10/S)
- Oven Cleaner and Shield Protectant (CL10, SH10)

Service

All products are backed by the ACP, Inc.
24/7 ComServ Support Center

Warranty

Warranty Certificate for this product can be found on the ACP, Inc. website at www.acpsolutions.com/warranty

Safety and Sanitation

This ACP, Inc. product meets and exceeds safety and sanitation standards set for commercial microwave ovens by UL, ETL, NSF, CSA, and FDA.




AIA File #:

Specification #:



© 2021 ACP, Inc.
Cedar Rapids, Iowa 52404



Drawings available from KCL CADlog - techs@kclcad.com

Dimensions

		STYLE A	STYLE B
Exterior	Height	15" (381)	15" (381)
	Width	17 5/8" (439) ‡	17 5/8" (439) ‡
	Depth†	21 5/8" (549)†	22 5/8" (574)†
Cavity	Height	6 3/4" (171)	6 3/4" (171)
	Width	13" (330)	13" (330)
	Depth	12" (305)	12" (305)
Usable Cavity Space		0.6 cubic ft. (17 liter)	0.6 cubic ft. (17 liter)
Door Depth		36" (914), 90°+ door open	37" (940), 90°+ door open
Installation Clearance	Top	2" (51)	2" (51)
	Sides	1" (25)	1" (25)
	Back	None	None
Shipping Carton	Height	19 1/8" (485.8)	19 1/8" (485.8)
	Width	22" (558.8)	22" (558.8)
	Depth	25 1/2" (647.7)	25 1/2" (647.7)
Weight			
Product Weight		Ship weight (approx.)	UPS Shippable
71 lbs (32.2kg)		77 lbs (34.9kg)	Yes, ISTA 1A

Measurements are US Standard. Measurements in () are in millimeters

* IEC 60705 Tested

† Includes handle

‡ Includes filters

Features

Configuration	Countertop or shelf
Stackable	Yes
Display	LCD
Control System	Touchpad
Programmable Control	Yes, 10 pads
Braille	Overlay available
Settings Programmable	100
Max. Cooking Time	60:00
Microwave Distribution	Double rotating antennas, top and bottom
Power Levels	11
Defrost	Yes, power level 2
Time Entry Option	Yes
Multiple Portion Setting	Yes, X2 by default, optional up to X9
Stage Cooking	4 stages
Interior Light	Yes, LED
Automatic Voltage Sensor	Yes (North America only >1200W)
Air Filter	Yes, 2 removable
Signal	End of cycle, adjustable
Door Handle	Grab & Go
Exterior Finish	Stainless steel
Interior Finish	Stainless steel with gasket sealed borosilicate tray

Electrical Configuration

Region	Model#/ UPC	Automatic Voltage Sensor	Exterior Depth Style	Power Consumption	Power Output (microwave)	Power Source	Plug Configuration	Cord Length	Frequency	Magnetron
North America single phase	MDC10Y15 728028470987	No	A	1610W, 14.4 A	1000W*	120V, 60Hz, 15A, single phase	NEMA 5-15P	5 ft. (1.5m)	2450MHz	2
North America single phase	MDC12YA2 728028471014	No	A	2000W, 16.8 A	1200W*	120V, 60Hz, 20A, single phase	NEMA 5-20	5.5 ft. (1.7m)	2450MHz	2
North America single phase	MDC18Y2 728028471021	Yes	A	3000W, 14.4 A	1800W*	208/240V, 60Hz, 20A, single phase	NEMA 6-20	5.5 ft. (1.7m)	2450MHz	2
North America single phase	MDC21Y2 728028471144	Yes	B	3400W, 17.5 A	2100W*	208/240V, 60Hz, 20A, single phase	NEMA 6-20	5.5 ft. (1.7m)	2450MHz	2



225 49th Ave. Dr. SW, Cedar Rapids, IA 52404 U.S.A.
800-233-2366 • 319-368-8120 • Fax: 319-368-8198
www.acpsolutions.com

Part No. 20271314

Updated 1/21/2021

© 2021 ACP, Inc., Cedar Rapids, Iowa 52404

an Ali Group Company



The Spirit of Excellence